



Inductive sensor with selective performance Bi4FE-EM18HE-AP6X2-H1141



- threaded barrel, M18 x 1
- long version
- stainless steel, 1.4301
- front cap made of Duroplast, especially temperature and impact resistant
- detects ferromagnetic metals only
- 3-wire DC, 10...30 VDC
- normally open pnp output
- connector, M12 x 1

Wiring diagram



Function principles


Inductive proximity switches are designed for wear-free non-contact detection of metal objects. For this they use a high-frequency electro-magnetic AC field that interacts with the target. This field is generated by ferrite-less 3-coil system. Inductive sensors with selective features are only capable of detecting ferrous metals.

Type	Bi4FE-EM18HE-AP6X2-H1141
Ident-No.	1640232
Rated operating distance S_n	4 mm
Mounting mode	flush
Hysteresis (switching distance)	3... 15 %
Min. repeat accuracy	≤ 2 %
Temperature drift	≤ ± 10 %
Operating temperature	0 ... + 60 °C
Rated operational voltage (DC) U_B	10... 30 VDC
Max. ripple	≤ 10 % U_{pp}
Rated operational current (DC) I_e	≤ 200 mA
No-load current I_0	≤ 15 mA
Max. OFF-state current	≤ 0,1 mA
Max. switching frequency	≤ 2,5 kHz
Rated insulation voltage	≤ 0,5 kV
Output function	3-wire, normally open, PNP
Short-circuit protection	yes, cyclic
Max. voltage drop at I_e	≤ 1,8 V
Wire breakage / reverse polarity protection	yes / complete
Protection class	□
Housing style	threaded barrel; M18 x 1
Dimensions	72 mm
Housing material	metal, A2 1.4301 (AISI 304)
Active face	plastic, Duroplast
Max. fixing torque of coupling nut	25 Nm
Wiring	connector, M12 x 1
Vibration resistance	55 Hz (1 mm)
Shock resistance	30 x g (11 ms)
Degree of protection	IP67
Supply voltage indication	LED green
Switching status indication	LED yellow

Inductive sensor with selective performance Bi4FE-EM18HE-AP6X2-H1141


Mounting instructions	minimum gap
Gap D	2 x B
Gap W	3 x Sn
Gap T	3 x B
Gap S	1,5 x B
Gap G	6 x Sn

Diameter of active face B \varnothing 18 mm



Inductive sensor with selective performance Bi4FE-EM18HE-AP6X2-H1141

Accessories

Typ	Ident-No.	Description	Dimension drawing
QM-18	6945102	quick-mount fixing clamp with dead-stop; material: chrome-plated brass external thread M24 x 1,5.	
BST-18B	6947214	fixing clamp with dead-stop; material: PA6	